

## 42" SIDE BY SIDE REFRIGERATOR WITH STAINLESS GLASS DOOR

# TR-42SBS-SG-B

# FEATURES

- Balanced, forced-air refrigeration system enables proper airflow and even temperature throughout to keep food fresh.
- Industry exclusive, 300-series stainless steel interior and exterior.
- All stainless steel, beautifully crafted proud hinges pass True's rigorous one million door opening test.
- Beautifully crafted glass door with stainless steel frame, 120° stay-open feature and ergonomically designed, robust, tubular handles.
- Commercially inspired lift-up grill on top of the unit with toe kick that complements the look of True's undercounter units.
- Ramp-up, showcase interior LED lighting provides amazing illumination throughout.
- Intuitive True Precision<sup>®</sup> Control and readout provides digital accuracy and easy operation.
- Dual evaporator and dual compressor enables dedicated cooling systems for each zone.

# ORGANIZATION

### Refrigerator

- 3 adjustable/removable stainless steel encapsulated glass shelves.
- 1 fixed stainless steel encapsulated glass shelf.
- 3 full-extension, soft-close drawer bins.

### Freezer

- 3 adjustable/removable electro-polished stainless steel wire shelves.
- 1 fixed electro-polished stainless steel wire shelf.
- 3 full-extension, soft-close wire bins.

# **BUILD YOUR TRUE**

Customize your True with a variety of finish and hardware options at **true-residential.com/custom**.





TR-42SBS-SG-B

# SPECIFICATIONS

Dimensions (w x h x d)	42" x 84" x 24"
Cutout Dimensions (w x h x d) Flush Opening Standard Opening	42¼" x 84¼" x 26" 41¾" x 84" x 24"
Capacity (cu. ft.) – Refrigerator Capacity (cu. ft.) – Freezer	15.7 8.74
Temperature. Range — Refrigerator Temperature. Range — Freezer	33°F - 42°F -4°F - 4°F
Weight (lbs.)	720
Voltage	115/60/1 115/60/1 NEMA-5-15R
Amps	5.2
Annual Energy Consumption (kwh)	562
Power Cord Length (ft.)	9
Energy Star Rated	_

2001 East Terra Lane | O'Fallon, MO 63366-4434 | p636.240.2400 | f636.272.7546 | true-residential.com | info@true-residential.com


Specifications subject to change without notice.



### 30 15/32" [774mm] TR-42SBS-SG-B 27 29/32" 2 9/16" [65mm] [709mm] 25 25/32 42" [1067mm] [655mm] 13 1/32" 17 5/32" [331mm] [436mm] 41 9/16" [1056mm] 67 29/32" [1725mm] 83 15/16" [2132mm] Π DOOR HEIGHT 1L 23 25/32" 50 3/8" [1280mm] [604mm] 72 21/32" [1845mm] 26 5/8" 20 13/16" 18 25/32" [528mm] [477mm] [676mm] 24 19/32" [625mm] 3 15/16"

[100mm]

FRONT






# **OPENING DIMENSIONS**


### FLUSH OPENING

• • • • • • • • • • • • •		
WIDTH	HEIGHT	DEPTH
42¼"	84¼"	26"
• • • • • • • • • • • • •		

### **STANDARD OPENING**

WIDTH	HEIGHT	DEPTH
41¾"	84"	24"
• • • • • • • • • • • • •		





# **MODEL OPTIONS**

MODEL	FINISH
TR-42SBS-SG-B	Stainless glass door
TR-42SBS-SS-B	Stainless solid door

# **ACCESSORIES (OPTIONAL)**

- Side panel(s)
- Joining kits
- . . . . . . . . . . . . . . . .

# WARRANTY

3 year full (parts & labor) 6 year sealed system (parts & labor) 7-12 year (parts only - sealed system on registered products)

Specifications subject to change without notice.